

AMENDMENT TO THE CLAIMS**IN THE CLAIMS:**

Please **AMEND** claims 1, 7, 9, 10, 12, 14-16, 19, 20, 22, 29, 31, 34 and 35 as follows.

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A wheel speed sensor comprising:
a detection element having at least one lead, for detecting a wheel speed;
at least one terminal portion connected to the lead of the detection element;
a holder portion having a detection element fitting portion fitting the detection element therein and a terminal portion fitting portion fitting the terminal portion therein;
a rod-like projection projectedly formed on the holder portion;
an electric wire welded on the terminal portion; and
a resin sealed portion sealing the holder portion in a state that the detection element and the terminal portion are held in the holder portion and the electric wire is connected with the terminal portion,
wherein the detection element fitting portion and the terminal portion fitting portion are disposed such that the lead of the detection element is in proximity to a predetermined location of the terminal portion when the detection element and the terminal portion are fitted in the detection element fitting portion and the terminal portion fitting portion, respectively.
2. (Original) The wheel speed sensor according to claim 1, wherein the lead of the detection element and the predetermined location of the terminal portion are connected to each other by welding.

3. (Original) The wheel speed sensor according to claim 1, wherein a bent portion is formed in the predetermined location of the terminal portion.

4. (Original) The wheel speed sensor according to claim 1, wherein the detection element is disposed on an end portion of the holder portion.

5. (Previously Presented) The wheel speed sensor according to claim 1, wherein the holder portion further comprises an accommodating groove accommodating the lead of the detection element, the terminal portion fitting portion being formed below the accommodating groove.

6. (Original) The wheel speed sensor according to claim 1, wherein the terminal portion fitting portion comprises a plurality of terminal portion fitting portions, and wherein the holder portion includes a shielding plate formed between the adjacent terminal portion fitting portions.

7. (Currently amended) The wheel speed sensor according to claim 1, wherein the terminal portion is made of a metal, wherein the terminal portion includes a holding portion formed in the vicinity to a location of the terminal to which the electric wire is welded, for holding the electric wire in a bundled state, and an end of the terminal portion is fitted into the terminal portion fitting portion of the holder portion.

8. (Original) The wheel speed sensor according to claim 7, wherein the holding portion is a notch holding the electric wire therein.

9. (Currently Amended) The wheel speed sensor according to claim 7, wherein the terminal portion is formed into a substantially flat plate with at least one bend portion, and

wherein the terminal portion comprises a weld portion to which the electric wire is welded and a holding piece which is bent from the weld portion at a position where a distal end of the electric wire is located when the electric wire is welded to the weld portion, and

wherein the holding portion is formed in the holding piece.

10. (Currently Amended) A wheel speed sensor comprising:
a detection element for detecting a wheel speed;
at least one terminal portion connected to the detection element;
a holder portion holding the detection element and the terminal portion;
an electric wire welded on the terminal portion;
a resin sealed portion sealing the holder portion in a state that the detection element and the terminal portion are held in the holder portion and the electric wire is connected with the terminal portion; and

a rod-like projection projectedly formed on the holder portion,

wherein the holder portion is sealed with the resin sealed portion, and the rod-like projection has an outer end supporting the holder portion in a floating fashion and an end which does not project outwardly of the resin sealed portion.

11. (Original) The wheel speed sensor according to claim 10, wherein the rod-like projection has a polygonal cross section.

12. (Currently Amended) The wheel speed sensor according to claim 11, wherein the rod-like projection ~~is a rod provided on~~ extends from a bottom surface of the holder portion.

13. (Original) The wheel speed sensor according to claim 10, wherein the detection element is disposed on an end portion of the holder portion.

14. (Currently Amended) ~~The wheel speed sensor according to claim 10, A~~
wheel speed sensor comprising:

a detection element for detecting a wheel speed;

at least one terminal portion connected to the detection element;

a holder portion holding the detection element and the terminal portion;

an electric wire welded on the terminal portion;

a resin sealed portion sealing the holder portion in a state that the detection element and the terminal portion are held in the holder portion and the electric wire is connected with the terminal portion; and

a rod-like projection projectedly formed on the holder portion,

wherein the holder portion is sealed with the resin sealed portion, and the rod-like projection has an outer end supporting the holder portion in a floating fashion and an end which does not project outwardly of the resin sealed portion, and

wherein a flange portion is formed in the outer end of the rod-like projection.

15. (Currently Amended) The wheel speed sensor according to claim 10, wherein a ~~front~~ surface of the resin sealed portion around the rod-like projection is formed in a concave surface.

16. (Currently Amended) The wheel speed sensor according to claim 10, wherein the terminal portion is made of a metal,

wherein the terminal portion includes a holding portion formed in the vicinity to a location of the terminal to which the electric wire is welded, for holding the electric wire in a bundled state, and an end of the terminal portion is fitted into a terminal portion fitting portion of the holder portion.

17. (Original) The wheel speed sensor according to claim 16, wherein the holding portion is a notch holding the electric wire therein.

18. (Previously Presented) The wheel speed sensor according to claim 16, wherein the terminal portion is formed into a substantially flat plate with at least one bend portion, and

wherein the terminal portion comprises a weld portion to which electric wire is welded and a holding piece which is bent from the weld portion at a position where a distal end of the electric wire is located when the electric wire is welded to the weld portion, and

wherein the holding portion is formed in the holding piece.

19. (Currently Amended) A wheel speed sensor comprising:

a detection element for detecting a wheel speed;

at least one terminal portion connected to the detection element;

a holder portion holding the detection element and the terminal portion;

an electric wire welded on the terminal portion;

a resin sealed portion sealing the holder portion in a state that the detection element and the terminal portion are held in the holder portion and the electric wire is connected with the terminal portion; and

a rod-like projection projectedly formed on the holder portion, the rod-like ~~portion~~ projection being adapted to support the holder portion in a floating fashion when the holder portion is sealed with the resin sealed portion, the rod-like projection being positioned without projecting from a surface of the resin sealed portion.

20. (Currently Amended) The wheel speed sensor according to claim 19, wherein the terminal portion is made of a metal,

wherein the terminal portion includes a holding portion formed in the vicinity to a location of the terminal to which the electric wire is welded, for holding the electric wire in a bundled state, and an end of the terminal portion is fitted into a terminal portion fitting portion of the holder portion.

21. (Original) The wheel speed sensor according to claim 20, wherein the holding portion is a notch holding the electric wire therein.

22. (Currently Amended) The wheel speed sensor according to claim 20, wherein the terminal portion is formed into a substantially flat plate with at least one bend portion, and

wherein the terminal portion comprises a weld portion to which the electric wire is welded and a holding piece which is bent from the weld portion at a position where a distal end of the electric wire is located when the electric wire is welded to the weld portion, and

wherein the holding portion is formed in the holding piece.

Claims 23-28 (Cancelled).

29. (Currently Amended) ~~The wheel sensor according to claim 1,~~ A wheel speed sensor comprising:

a detection element having at least one lead, for detecting a wheel speed;
at least one terminal portion connected to the lead of the detection element;
a holder portion having a detection element fitting portion fitting the detection element therein and a terminal portion fitting portion fitting the terminal portion therein;
an electric wire welded on the terminal portion; and
a resin sealed portion sealing the holder portion in a state that the detection element and the terminal portion are held in the holder portion and the electric wire is connected with the terminal portion.

wherein the detection element fitting portion and the terminal portion fitting portion are disposed such that the lead of the detection element is in proximity to a predetermined location of the terminal portion when the detection element and the terminal portion are fitted in the detection element fitting portion and the terminal portion fitting portion, respectively, and

wherein the detection element fitting portion is a partially cutaway cylinder such that a main portion of the detection element fits in ~~the~~ an interior ~~therein~~ thereof with no gap being formed between the interior and the main portion.

30. (Previously Presented) The wheel sensor according to claim 29, wherein the terminal portion fitting portion is an outward extension extending from the partially cutaway cylinder.

31. (Currently Amended) The wheel sensor according to claim 30, wherein the outward extension includes an accommodating groove for accommodating the lead of the detection element and a fitting portion located below the accommodating groove for accommodating the terminal portion.

32. (Previously Presented) The wheel sensor according to claim 3, wherein the lead makes contact with the bent portion of the terminal portion at the predetermined location.

33. (Previously Presented) The wheel sensor according to claim 1, wherein the terminal portion includes a notch having an opening end having a larger diameter portion and a weld portion end having a smaller diameter portion.

34. (Currently Amended) The wheel sensor according to claim 8, wherein the notch is formed such that ~~the~~ a diameter is reduced in a gradual or stepped fashion from a larger diameter portion at an open end toward a smaller diameter portion.

35. (Currently Amended) The wheel sensor according to claim 10, wherein the holder portion includes a detection element fitting portion which is a partially cutaway cylindrical configuration such that a main portion of the detection element fits in ~~the~~ an

interior ~~therein~~ thereof with no gap being formed between the interior and the main portion.

36. (Previously Presented) The wheel sensor according to claim 35, wherein the holder portion further includes a terminal portion fitting portion which is an outward extension extending from the partially cutaway cylindrical configuration.